

WHEATSHEAF HOTEL SOUND SPECIFICATIONS

FOH Speaker System

2 x Clair Brothers Audio F28V
1 x Clair Brothers RC80 – out fill
2 x Bag End SE18-C- subs
1 x Clair Brothers D 40:4L amplifier

FOH Mixing Console

1 x Allen & Heath QU-24

MONITOR Speaker System

3 x EAW SM-155Hi
1 x RCF 15" + horn drum monitor
ON SEPARATE SENDS
2 x CAH 2002 Amplifier

Microphones / DI's

6 x Shure Beta58
6 x Shure SM57
1 x Shure Beta 52A
2 x Shure 57A
4 x Rode M5
2 x Behringer Ultra DI
4 x Palmer Pro DI

Microphone Stands

8x Tall Boom
6 x Short Boom
2 x LP Drum Claw

Microphone Cables

24x Microphone Cable (6m)

Stage Specifications

Full In-house PA with all mics, leads, stands
Width: 6.54m at widest point
Depth: 3.8m
Floor to Stage: raised 0.4m
Stage to Ceiling: 2.1m
Power: 240V
Lighting Bars: 4 spots
Basic Lighting
Small storage area at rear of stage.

Cabaret seating - No Kitchen or meals - No Accommodation - No dressing room

Additional Information Band Room Capacity: 100 Hotel Max. Capacity: 32